

Nano Insulating Castable Material Ultra Lightweight Lightweight Castable Refractory

Basic Information • Place of Origin: Zhengzhou, Henan, China • Brand Name: • Certification:

- Model Number:
- Minimum Order Quantity:
 - 200-800 USD
- Packaging Details:

• Price:

- Delivery Time:
 - TT; L/C
- Supply Ability:

Rongsheng Xinwei

- ISO Certification
- RS-CQJ0.35, RS-CQJ0.45, RS-CQJ0.5
- 1 Ton

20-30DAYS

packed on wooden pallets, with water-proof cover, and tightened with plastic/steel bandages

• Payment Terms:

2000tons /month

Product Specification

 Acid Resistance: 	No Degradation
 Alkali Resistance: 	No Degradation
Compressive Strength:	0.4MPa
Elongation:	300%
 Flammability: 	Class A1
Material:	Nano Insulation Material
Radiation Resistance:	No Degradation
 Smoke Density: 	Class 0
• Temperature Resistance:	-50 ~+150
 Tensile Strength: 	2.0MPa
 Thermal Conductivity: 	0.038W/mK
 Thermal Resistance: 	0.26m2K/W
Thickness:	1mm
Water Vapor Permeability:	2.0g/m2/24h
• Weight:	100g/m2

Product Description

Ultra-lightweight Insulating Castable Series

The ultra-lightweight insulating castable developed by Rongsheng is made of high-temperature high-strength light-weight nano-aggregate, aluminate cement and high-alumina fines with various additives, which has the advantages of small bulk density, high crushing strength, low thermal conductivity, excellent thermal insulation, energy saving and consumption reduction, convenient construction, and so on. It can reduce the thermal energy consumption of industrial furnaces and reduce the weight of furnace lining.

Parameter of Ultra-lightweight Insulating Castable Series

Items		RS-CQJ0.35	RS-CQJ0.45	RS-
BD, g/cm3	110 ×24h	≤0.35	≤0.45	5

CCS, MPa	110 ×24h	≥0.5	≥0.8	2
TC,W/(m·K)	350 ±25	≤0.11	≤0.15	5
 PLC,%	1 1	-0.1~+0.1 1000 ×12h	-0.1~+0.1 1100 ×12h	-0.2~+0.2
 Max Working Temperature,		1000	1100	1
Sourcest et le chaver Henan Rongs	sheng Xinwei Ne	w Materials Research Institu	ite Co., Ltd	