

Refractory Factory Production Ceramic Fiber Rope Ceramic Fiber Cord Low Density

Our Product Introduction

for more products please visit us on bricksrefractory.com

Basic Information

- Place of Origin: Zhengzhou, Henan, China
- Brand Name: Rongsheng Xinwei
- Certification: ISO Certification
- Model Number: Ceramic fiber round braided rope, Ceramic fiber square braided rope
- Minimum Order Quantity: 5 Kilograms
- Price: \$1.80 - \$6.00
- Packaging Details: 1. Carton with inner PVC bags carton.
2. Woven bags with inner PVC bags.
- Delivery Time: 10-20 Days
- Payment Terms: TT; L/C
- Supply Ability: 30 Metric Ton/Metric Tons Per Day



Product Specification

- Color: White
- Cost: Cost-Effective
- Density: Low Density
- Durability: High Durability
- Flexibility: High Flexibility
- Insulation: Excellent Insulation
- Length: Various Lengths
- Material: Ceramic Fiber
- Resistance: High Resistance
- Shape: Various Shapes
- Size: Various Sizes
- Surface: Smooth Surface
- Temperature: High Temperature
- Thickness: Various Thickness
- Width: Various Widths

Our Product Introduction

Product Description

Description of Good Price Refractory Factory Production Ceramic Fiber Rope

Ceramic fiber rope is made from high quality ceramic fiber yarn, with light weight, good flexibility. It has two types, glass filament reinforced and stainless steel reinforced, can be widely used in industrial heat insulation.

Features of Ceramic Fiber Rope

1. High density, neat and delicate.
2. Quality material selection, strict workmanship.
3. Has good corrosion resistance.

Applications Of Ceramic Fiber Rope

Industrial furnace, used for industrial furnace curtain, furnace door seal

High temperature cable, pipeline wrapping
 Metallurgy, power petrochemical industry
 Fire doors, fire curtains, fire blankets, spark MATS and thermal insulation coverings

Parameter of Refractory Factory Production Ceramic Fiber Rope

Classification temperature	1260			
Name	Ceramic fiber round braided rope		Ceramic fiber square braided rope	
Brand	XSY-A	XSY-B	XSF-A	X
Main material	Ceramic fiber/glass fiber	Ceramic fiber/stainless steel wire	Ceramic fiber/glass fiber	Ceramic fiber/stainless steel wire
Bulk Density kg/m ³	500			
Size	200000/50000×10/25/30		10000×(20×20/30×30)	
Long term service temperature	650	1050	600	1050
Moisture content %	≤2			
Organic content %	≤15			



Henan Rongsheng Xinwei New Materials Research Institute Co., Ltd



+86-18538509097



Jackyhan2023@outlook.com



bricksrefractory.com

11th Floors, Building 6, China Central Electronic Commerce Port, Daxue Road, Zhengzhou, Henan, China