


## Pottery Kiln Ceramic Fiber Products Polycrystalline Mullite Ceramic Fiber Board

Our Product Introduction

for more products please visit us on [bricksrefractory.com](http://bricksrefractory.com)

### Basic Information

- Place of Origin: Zhengzhou, Henan, China
- Brand Name: Rongsheng Xinwei
- Certification: ISO Certification
- Model Number: Rongsheng Polycrystalline Mullite Fiber Board
- Minimum Order Quantity: 50 Rolls
- Price: 10-15USD
- Packaging Details: Carton with inner PVC bags carton
- Delivery Time: 10-20 Days
- Payment Terms: TT; L/C
- Supply Ability: 25000 Rolls Per Day ceramic fiber blanket



### Product Specification

- Chemical Resistance: Excellent
- Color: White
- Compressive Strength: 2.5-3.5 MPa
- Density: 128-160 Kg/m<sup>3</sup>
- Flexural Strength: 2.5-3.5 MPa
- Material: Ceramic Fiber
- Melting Point: 1400-1500°C
- Moisture Content: ≤1%
- Tensile Strength: 2.5-3.5 MPa
- Thermal Conductivity: 0.09-0.15 W/m.K
- Thermal Expansion: 0.5-1.0 X 10<sup>-6</sup>/K
- Thermal Shock Resistance: Excellent
- Thermal Stability: Excellent
- Highlight: Pottery Kiln Ceramic Fiber Products, Ceramic Fiber Board Pottery Kiln, Polycrystalline Mullite Ceramic Fiber Board



### More Images



### Product Description

#### Description of Polycrystalline Mullite Fiber Board

Polycrystalline mullite fiber board is made of polycrystalline mullite fiber cotton compressed together using organic and inorganic adhesives by wet vacuum suction filter process. Fiber board has characteristics of excellent strength, anti-scouring, easy processing and cutting. As a multi-purpose product, polycrystalline mullite fiber board can be applied to high temperature heat surface of furnace lining.

#### Features of Polycrystalline Mullite Fiber Board

- Low heat capacity and low thermal conductivity
- Non-brittle material, good elasticity
- Excellent thermal stability
- Resisting wind erosion, long service life
- Excellent thermal shock resistance
- Excellent spalling resistance performance
- Easy to be molded and cut

#### Applications of Polycrystalline Mullite Fiber Board

Our Product Introduction

High temperature sealing gasket  
 Anti-scour parts of lining inner paste  
 Hot surface material of high temperature furnace lining  
 Heating device thermal insulation  
 Furnace door and body filling material

**Parameter of Polycrystalline Mullite Fiber Board**

Item		Index
Al <sub>2</sub> O <sub>3</sub> %		72~75
Al <sub>2</sub> O <sub>3</sub> +SiO <sub>2</sub> %		99
Fe <sub>2</sub> O <sub>3</sub> %		0.1
Classification temperature		1600
Bulk Density Kg/m <sup>3</sup>		Loose cotton, 56; Trim block, 100; Stacking block
Permanent Linear Change Rate % 1500 ×6h		1
Thermal Conductivity W/(m·K)	1000	0.226
	1400	0.387
Melting Point		1840



**Henan Rongsheng Xinwei New Materials Research Institute Co., Ltd**



+86-18538509097



Jackyhan2023@outlook.com



bricksrefractory.com

11th Floors, Building 6, China Central Electronic Commerce Port, Daxue Road, Zhengzhou, Henan, China