Our Product Introdu

High Strength High Alumina Refractory Bricks Bauxite Fire Brick With High Thermal Stability & Fire Resistance

Basic Information

• Place of Origin: Zhengzhou ,China . Brand Name: Rongsheng Xinwei

• Certification: ISO9001

Model Number: RS-48, RS-55, RS-65, RS-75, RS-80

 Minimum Order Quantity: 1 Ton • Price: 200-800USD

 Packaging Details: packed on wooden pallets, with water-proof

cover, and tightened with plastic/steel bandages

20-30DAYS • Delivery Time: • Payment Terms: TT; L/C

• Supply Ability: 2000tons /month



Product Specification

• Bulk Density: • Chemical Resistance: High · Color: White • Compressive Strength: High Density: High

Material: High Alumina Refractory Brick Low

• Refractoriness: High • Refractoriness Under Load: High Shape: Rectangular Size: Standard • Softening Temperature: • Thermal Conductivity: Low • Thermal Expansion: Low • Thermal Shock Resistance: High



More Images

• Porosity:





Product Description

Brief Introduction of High Strength High Alumina Refractory Bricks Bauxite Fire Brick With High Thermal Stability & Fire Resistance

High alumina brick is a kind of neutral refractory with alumina content above 48%. It is formed by shaping and calcining bauxite or other raw materials with high alumina content. High thermal stability and fire resistance above 1770

The production process of high alumina bricks is similar to that of multi clinker clay bricks. The difference is that the proportion of clinker in the ingredients is high, up to 90~95%. Before crushing, the clinker needs to be sorted and screened to remove iron. The firing temperature is high. For example, when high alumina bricks such as I and II are fired in tunnel kilns, it is generally 1500~1600



Feature of High Strength Aluminum Refractory Brick

- 1. Good thermal conductivity.
- 2. High fire resistance.
- 3. Good slag resistance, acid and alkali resistance.
- 4. Thermal stability.

Appliaction Of High Alumina Refractory Bricks

As a basic material in the field of high-temperature technology, high alumina bricks are widely used in cement, glass building materials, steel smelting, petrochemical and other industries. High temperature industrial furnaces for high alumina bricks include blast furnace, not blast furnace, electric furnace, blast furnace, reverberatory furnace and rotary kiln lining. In addition, high alumina bricks can also be processed into open hearth regenerative grid bricks, socket bricks for pouring system, nozzle bricks, etc. according to the requirements of industrial furnaces.

Product Specification of High Alumina Refractory Bricks

Froduct Specification of riight Aldinina Heriactory Brick	.5				
Item	Specification				
	LZ-80	LZ-75	LZ-70	LZ-65	LZ-55
Al2O3 %	≥80	≥75	≥70	≥65	≥55
Apparent Porosity, %	≤21	≤24	≤24	≤24	≤22
CCS, MPa	≥70	≥60	≥55	≥50	≥45
0.2MPa RUL	≥1530	≥1520	≥1510	≥1500	≥1450
PLC, %	1500 ×2h		1450 ×2h		
	-0.4~0.2		-0.4~0.1		



11th Floors, Building 6, China Central Electronic Commerce Port, Daxue Road, Zhengzhou, Henan, China