

2-3cm Fireclay Glazed Brick For Kilns And Furances

for more products please visit us on bricksrefractory.com

Basic Information	
• Place of Origin:	Zhengzhou ,China
 Brand Name: 	Rongsheng Xinwei
Certification:	ISO9001
 Model Number: 	SK-32, SK-34, SK-36
Minimum Order Quantity:	1 Ton
• Price:	200-800USD
Packaging Details:	packed on wooden pallets, with water-proof cover, and tightened with plastic/steel bandages
Delivery Time:	10-20 Days

• Delivery Time:

- Payment Terms: TT; L/C 2000tons /month
- Supply Ability:

Product Specification

Chemical Resistance: High Color: Yellow Compressive Strength: High High Density: Durability: Long-lasting • Frost Resistance: High • Heat Resistance: High Material: Clay Shape: Rectangle Size: Standard • Surface: Smooth • Texture: Hard • Thickness: 2-3cm Steel, Nonferrous Metals, Glass, Cement, • Usage: Ceramics, Pertrifaction, Machinery, Boiler,

More Images



Product Description

Introduction of High Quality Refractory Arch Brick Low Porosity Refractory Fire Clay Brick For Kilns And Furances Fireclay brick is made from clinker clay by mixing, forming, drying, sintering and matching characterized by good resistance to corrosion and abrasion, good thermal shock resistance, good spelling resistance, high mechanical strength, good volume stability under high temperature.



Product Features of Low Porosity Refractory Fire Clay Brick Low porosity, Excellent corrosion resistance High refractoriness, High-temperature endurance. Good spalling resistance and wear resistance.Good volume stability at high temperature.

Application of Fire Clay Brick Low porosity clay bricks can be applied to steel, nonferrous metals, glass, cement, ceramics, pertrifaction, machinery, boiler, light industry, electric power, war industry and other economic filed, which is the indispensable basic material to ensure above production running and technological development, it plays an incomparable important role in the development of high temperature industrial production.

Rongsheng Refractory Fire Clay Brick Technical Data

Item	Fire Clay Brick SK-32	Fire Clay Brick SK-34	Fire Clay
AI2O3(%)	30	38	
Fe2O3 (%)	3	2.5	
Refractoriness (SK)	32	34	1
Refractoriness under load, 0.2MPa, Ta, ((°C)	1300	1350	
Porosity (%)	22-26	19-23	1
Bulk density (g/cm ³)	2.05	2.10-2.15	2.3
Cold crushing strength (MPa)	25	25	
Thermal expansion at 1000°C (%)	0.6	0.6	

Henan Rongsheng Xinwei New Materials Research Institute Co., Ltd ۲

+86-18538509097 Jackyhan2023@outlook.com bricksrefractory.com

11th Floors, Building 6, China Central Electronic Commerce Port, Daxue Road, Zhengzhou, Henan, China