for more products please visit us on bricksrefractory.com

Refractory Factory Production Ceramic Fiber Rope Ceramic Fiber Cord Low Density

Basic Information

Place of Origin: Zhengzhou, Henan, China
 Brand Name: Rongsheng Xinwei
 Certification: ISO Certification

Model Number: Ceramic fiber round braided rope, Ceramic

fiber square braided rope

Minimum Order Quantity: 5 KilogramsPrice: \$1.80 - \$6.00

• Packaging Details: 1.Carton with inner PVC bags carton.

2. Woven bags with inner PVC bags.

Delivery Time: 10-20 DaysPayment Terms: TT; L/C

• Supply Ability: 30 Metric Ton/Metric Tons Per Day



Product Specification

· Color: White • Cost: Cost-Effective Density: Low Density Durability: High Durability Flexibility: High Flexibility • Insulation: **Excellent Insulation** Length: Various Lengths Material: Ceramic Fiber • Resistance: High Resistance Shape: Various Shapes Size: Various Sizes Surface: Smooth Surface • Temperature: High Temperature • Thickness: Various Thickness • Width: Various Widths

Product Description

Description of Good Price Refractory Factory Production Ceramic Fiber Rope

Ceramic fiber rope is made from high quaility ceramic fiber yarn, with lighit weight, good flexibility. It has two type, glass filament reinforced and stainless stainless steel reinforced, can be widely used in industrial heat insulation.

Features of Ceramic Fiber Rope

- 1. High density, neat and delicate.
- 2. Quality material selection, strict workmanship.
- 3. Has good corrosion resistance.

Applications Of Ceramic Fiber Rope

Industrial furnace, used for industrial furnace curtain, furnace door seal

High temperature cable, pipeline wrapping Metallurgy, power petrochemical industry Fire doors, fire curtains, fire blankets, spark MATS and thermal insulation coverings

Parameter of Refractory Factory Production Ceramic Fiber Rope

Classification temperature	1260					
Name	Ceramic fiber round braided rope		Ceramic fi		iber square braided ro	
Brand	XSY-A	XSY-B	XSF-A		X	
Main material	Ceramic fiber/glass fiber	Ceramic fiber/stainless steel wire	Ceramic fiber/glass fiber	er	Ceramic fiber/s	
Bulk Density kg/m ³	500					
Size	200000/50000×10/25/30		10000×(20×20/30×30)			
Long term service temperature	650	1050	600		1	
Moisture content %	≤2					
Organic content %	≤15					

Henan Rongsheng Xinwei New Materials Research Institute Co., Ltd

+86-18538509097 Jackyhan2023@outlook.com bricksrefractory.com

11th Floors, Building 6, China Central Electronic Commerce Port, Daxue Road, Zhengzhou, Henan, China