

## 65%-95% Al<sub>2</sub>O<sub>3</sub> Refractory Ball High Alumina Ceramic Ball For Heating Furnace

Our Product Introduction

for more products please visit us on [bricksrefractory.com](http://bricksrefractory.com)

### Basic Information

- Place of Origin: Zhengzhou ,China
- Brand Name: Rongsheng Xinwei
- Certification: ISO9001
- Model Number: RS-65 RS-70, RS-75, RS-95
- Minimum Order Quantity: 1 Ton
- Price: 200-800USD
- Packaging Details: packed on wooden pallets, with water-proof cover, and tightened with plastic/steel bandages
- Delivery Time: 20-30DAYS
- Payment Terms: TT; L/C
- Supply Ability: 2000tons /month



### Product Specification

- Al<sub>2</sub>O<sub>3</sub> Content: ≥48%
- Compressive Strength: ≥50MPa
- Density: 2.4-2.8g/cm<sup>3</sup>
- Fe<sub>2</sub>O<sub>3</sub> Content: ≤3.5%
- Material: High Alumina
- Porosity: ≤18%
- Refractoriness: ≥1700
- Refractoriness Under Load: ≥1400
- Thermal Expansion: ≤0.6%
- Thermal Shock Resistance: Good
- Type: Refractory Brick
- Application: Industrial Furnaces
- Color: Yellow
- Shape: Ball
- Size: Customized Size

Our Product Introduction

### Product Description

#### Factory Price Refractory Ball 65%-95% Al<sub>2</sub>O<sub>3</sub> High Alumina Ceramic Ball For Heating Furnace in The Iron and Steel Industry

Refractory balls are made of industrial alumina and refractory kaolin as the main raw materials, which are made by scientific formula, forming and high temperature calcination.

Refractory ball is divided into ordinary refractory ball and high aluminum resistance ball. Refractory porcelain ball high temperature resistance to high temperature can reach 1900 degrees, high mechanical strength and long-term use.

#### High Alumina Refractory Ball Features

1. high temperature resistant performance, the highest heat resistant ceramic ball temperature can reach 1900 degrees;
2. high mechanical strength, long use cycle;
3. good chemical stability, no chemical reaction with the material;
4. good thermal stability, high strength;

#### High Alumina Refractory Ball Applications

High alumina refractory ball application in chemical fertilizer plant of high and low temperature transformation furnace, reformer, hydrogenation, desulfurization tank and methanation furnace, dispersed liquid, and supporting, covering and

protecting catalyst role, can also be used in heating furnace of iron and steel industry and the transformation of equipment, ordinary refractory ball suitable for sulfuric acid and fertilizer industries converter and transform furnace, high aluminum refractory ball is suitable for industries such as steel, urea, hot blast furnace, heating and transformation furnace and other equipment.



**Product Specification of High Alumina Refractory Ball**

Item	High alumina	Low creep	Mullite	
Size(mm)	40-80	40-80	40-80	
AL <sub>2</sub> O <sub>3</sub> (%)	65	70	75	
Refractoriness under load(°C)	1450	1460	1530	
Apparent Porosity(%)	25	23	22	
Bulk Density(g/cm <sup>3</sup> )	2.3	2.4	2.5	
Cold crushing strength(Mpa)	13	14	32	
Thermal shock resistance (1100°Cwater cooling) cycle ≥	15	10	20	
Refractoriness(°C)	1710	1750	1800	



**Henan Rongsheng Xinwei New Materials Research Institute Co., Ltd**



+86-18538509097



Jackyhan2023@outlook.com



bricksrefractory.com

11th Floors, Building 6, China Central Electronic Commerce Port, Daxue Road, Zhengzhou, Henan, China