

Thin Fireclay Brick Round Curved Kiln Refractory Brick Clay Fire Bricks With 30-50% Al₂O₃ For Cement Industry

Our Product Introduction

for more products please visit us on bricksrefractory.com

Basic Information

- Place of Origin: Zhengzhou, Henan, China
- Brand Name: Rongsheng Xinwei
- Certification: ISO Certification
- Model Number: SK-30, SK-32, SK-34, SK-35
- Minimum Order Quantity: 1 Ton
- Price: 200-800 USD
- Packaging Details: packed on wooden pallets, with water-proof cover, and tightened with plastic/steel bandages
- Delivery Time: 10-20 Days
- Payment Terms: TT; L/C
- Supply Ability: 2000 tons /month



Product Specification

- Color: Yellow
- Durability: High
- Edge: Smooth
- Heat Resistance: High
- Material: Clay
- Name: Fireclay Brick
- Shape: Rectangle
- Size: Standard
- Surface: Glazed
- Texture: Smooth
- Thickness: 2 Cm
- Usage: Building
- Water Resistance: High
- Weight: 2 Kg
- Highlight: Thin Fireclay Brick, Fireclay Brick Round,



More Images



Product Description

Product Description of Thin Fireclay Brick Round Curved Kiln Refractory Brick Clay Fire Bricks With 30-50% Al₂O₃ For Cement Industry

The Fire Clay Brick contains an Al₂O₃ content ranging from 30% to 50%. In the production process, clay chamotte is initially blended with refractory clay powder. It is then mixed with clay aggregate to form dry mud, followed by high-pressure molding and sintering at approximately 1400°C. When subjected to high temperatures, these fire clay bricks exhibit a slightly acidic nature and demonstrate limited resistance to alkaline slag erosion. However, as the Al₂O₃ content increases, their thermal stability surpasses that of silica brick, magnesite brick, and similar materials.

Our Product Introduction



Product Features of Thin Fireclay Brick Round Curved Kiln Refractory Brick Clay Fire Bricks

- 1.High heat resistance
- 2.Low thermal conductivity
- 3.Durability:
- 4.Aesthetics
- 5.High compressive strength
- 6.Low water absorption
- 7.Chemical resistance

Product Application of Round Curved Kiln Refractory Brick Clay Fire Bricks With 30-50% Al₂O₃ For Cement Industry

- 1) Cement and other building materials industry kiln back insulation;
- 2) Petrochemical, metallurgical, ceramics, glass industry, the furnace lining insulation;
- 3)Heat treatment furnace backlash insulation;
- 4)Non-ferrous metal industry back insulation;
- 5)High temperature reaction, heating equipment back insulation insulation

Product Specification of Thin Fireclay Brick Round Curved Kiln Refractory Brick Clay Fire Bricks

Item/Grade	Fire Clay Brick					High Alumina t	
	SK-30	SK-32	SK-34	SK-35	SK-36	SK-37	S
AL ₂ O ₃ % (≥)	30	35	38	45	55	65	
Fe ₂ O ₃ % (≤)	2.5	2.5	2	2	2	2	
Refractoriness(SK)	30	32	34	35	36	37	
Refractoriness Under Load, 0.2MPa, °C (≥)	1250	1300	1360	1420	1450	1480	1
Apparent Porosity (%)	22-26	20-24	20-22	18-20	20-23	20-23	2
Bulk Density (g/cm ³)	1.9-2.0	1.95-2.1	2.1-2.2	2.15-2.22	2.25-2.4	2.3-2.5	2.
Cold Crushing Strength ,MPa (≥)	20	25	30	40	45	50	



Henan Rongsheng Xinwei New Materials Research Institute Co., Ltd



+86-18538509097



Jackyhan2023@outlook.com



bricksrefractory.com

11th Floors, Building 6, China Central Electronic Commerce Port, Daxue Road, Zhengzhou, Henan, China