

## Standard Size Fire Brick High Alumina Refractory Brick With 48%+ Alumina for High Temp Tunnel Kilns

Our Product Introduction

for more products please visit us on [bricksrefractory.com](http://bricksrefractory.com)

### Basic Information

- Place of Origin: Zhengzhou ,China
- Brand Name: Rongsheng Xinwei
- Certification: ISO9001
- Model Number: LZ-48, LZ-55, LZ-65, LZ-70, LZ-75, LZ-80
- Minimum Order Quantity: 1 Ton
- Price: 200-800USD
- Packaging Details: packed on wooden pallets, with water-proof cover, and tightened with plastic/steel bandages
- Delivery Time: 20-30DAYS
- Payment Terms: TT; L/C
- Supply Ability: 2000tons /month



### Product Specification

- Application Temperature:  $\leq 1400$
- Bulk Density: 2.2-2.6g/cm<sup>3</sup>
- Chemical Resistance: Good
- Color: White
- Compressive Strength:  $\geq 50$ MPa
- Packaging: Carton
- Porosity:  $\leq 20\%$
- Product Name: High Alumina Refractory Brick
- Raw Material: Alumina
- Refractoriness:  $\geq 1700$
- Shape: Brick
- Size: Customized
- Thermal Conductivity:  $\leq 1.2$ W/m.K
- Thermal Shock Resistance: Good
- Water Absorption:  $\leq 20\%$



### More Images



### Product Description

#### Product of Standard Size Fire Brick High Alumina Refractory Brick With 48%+ Alumina for High Temp Tunnel Kilns

High alumina brick, containing over 48% alumina, is classified as a neutral refractory. It is crafted through the molding and calcination of bauxite or similar high alumina raw materials. Exhibiting exceptional thermal stability, it withstands temperatures in excess of 1770 .

Our range encompasses top-grade High Alumina Bricks engineered to cater to the demands of neutral refractoriness, ensuring safe operation at temperatures surpassing 1300 degrees centigrade. Tailoring to specific needs, we offer High Alumina Bricks in various specifications to meet the unique requirements of our customers.

Our Product Introduction



#### Features of High alumina brick

- 1.High refractoriness
- 2.High load-bearing softening temperature
- 3.Good slag resistance
- 4.Good thermal stability
- 5.Low thermal conductivity
- 6.High strength
- 7.Good wear resistance
- 8.Good chemical stability
- 9.Wide range of use temperatures

#### HIGH ALUMINA BRICK



High alumina bricks are widely used in various industries due to their excellent properties, such as high refractoriness, good slag resistance, good thermal stability, low thermal conductivity, high strength, good wear resistance, and good chemical stability.

#### Applications of high alumina bricks:

Refractory linings for industrial furnaces and boilers, Cement kilns, Glass furnaces, Petrochemical and refinery plants, Metallurgical furnaces.

#### Product Specification of Standard size of fire brick high alumina refractory brick

Item	Index			
	SK40 LZ-80	SK38 LZ-75	SK37 LZ-65	SK36 LZ-55
Al <sub>2</sub> O <sub>3</sub> %	≥80	≥75	≥65	≥55
Apparent Porosity, %	≤21	≤24	≤24	≤22
CCS, MPa	≥70	≥60	≥50	≥45
0.2MPa RUL	≥1530	≥1520	≥1500	≥1450
PLC, %	1500 ×2h -0.4~0.2			1450 ×2h -0.4~0.1



**Henan Rongsheng Xinwei New Materials Research Institute Co., Ltd**



+86-18538509097



Jackyhan2023@outlook.com



[bricksrefractory.com](http://bricksrefractory.com)

11th Floors, Building 6, China Central Electronic Commerce Port, Daxue Road, Zhengzhou, Henan, China