Our Product Introduc

RP HP UHP Grades Available Graphite Electrode Nipples Dia 200-800mm For **Electric Arc Furnaces**

Basic Information

• Place of Origin: Zhengzhou ,China • Brand Name: Rongsheng Xinwei

• Certification: ISO9001 Model Number: Rongsheng Minimum Order Quantity: 1 Ton • Price: 200-800USD

• Packaging Details: Packed on wooden pallets, with water-proof

cover, and tightened with plastic/steel bandages

20-30Days • Delivery Time: • Payment Terms: TT; L/C • Supply Ability: 2000tons /month



Product Specification

• Highlight: RP Graphite Electrode Nipples

UHP Graphite Electrode Nipples , Electric Arc Furnaces Graphite Electrode

Product Description

Product Description of RP HP UHP Grades Available Graphite Electrode Nipples Dia 200-800mm For **Electric Arc Furnaces At Competitive Prices**

Discover our high-quality Graphite Electrode Nipples, specifically designed for use in electric arc furnaces. Available in diameters ranging from 150mm to 600mm, our nipples are crafted from premium carbon graphite, ensuring excellent performance and durability in high-temperature environments.



Key Features of RP HP UHP Grades Available Graphite Electrode

Exceptional Conductivity: Our graphite nipples provide outstanding electrical conductivity, facilitating efficient energy transfer during operations.

High-Temperature Resistance: Built to endure extreme thermal conditions, these nipples maintain their structural integrity for reliable use.

Robust Construction: Manufactured using high-grade materials, they are resistant to oxidation and wear, guaranteeing longevity.

Versatile Sizes: Offered in various diameters to accommodate your specific operational needs.

Applications of RP HP UHP Grades Available Graphite Electrode
Graphite electrode nipples are ideal for a range of applications, including:
Electric Arc Furnaces: Essential for steel production and metal recycling.

Industrial Furnaces: Suitable for various foundry applications. **Chemical Processes**: Used in the production of silicon and other compounds.

Technical Parameter of Graphite Electrodes and Nipple:

Regular Graphite Electrode

ltem		Nominal diameter mm							
		75~130		150~225		~300	~300 350~45		
Grade		<u> </u>	Ex	_	Ex	_	Ex		
Electrode	8.5	10.0	9.0	10.5	9.0	10.5	9.0	10.	
Connector	8.0		8.0		8.0		8.0		
Electrode	10.0	10.0		10.0		8.0		7.0	
Connector	15.0	15.0		15.0		15.0		15.0	
Electrode	9.3		9.3		9.3		9.3		
Connector	14.0		14.0		1	4.0	1	4.0	
Electrode	1.58		1.53		1.53		1.53		
Connector	1.70		1.70		1.70		1.70		
Electrode	2.9		2.9		2.9 2.9		-	2.9	
Connector	2.7		2.7		2.7 2.7 2.8		2.8	:	2.8
	0.5			0.5	(0.5		0.5	
	Connector Electrode Connector Electrode Connector Electrode Connector Electrode Electrode	Excellent Electrode 8.5 Connector 8.0 Electrode 10.0 Connector 15.0 Electrode 9.3 Connector 14.0 Electrode 1.58 Connector 1.70 Electrode 2.9 Connector 2.7	Excellent	Excellent — Ex Electrode 8.5 10.0 9.0 Connector 8.0 10.0 1 Electrode 10.0 1 1 Connector 15.0 1 1 Electrode 9.3 1 1 Connector 14.0 1 1 Electrode 1.58 1 1 Connector 1.70 1 1 Electrode 2.9 1 1 Connector 2.7 1 1	75~130 150~225 Excellent — Ex — Electrode 8.5 10.0 9.0 10.5 Connector 8.0 8.0 Electrode 10.0 10.0 Connector 15.0 15.0 Electrode 9.3 9.3 Connector 14.0 14.0 Electrode 1.58 1.53 Connector 1.70 1.70 Electrode 2.9 2.9 Connector 2.7 2.7	75~130 150~225 250 Excellent — Ex — Ex Electrode 8.5 10.0 9.0 10.5 9.0 Connector 8.0	75~130 150~225 250~300 Excellent — Ex — Ex — Electrode 8.5 10.0 9.0 10.5 9.0 10.5 Connector 8.0 <t< td=""><td>75~130 150~225 250~300 350 Excellent — Ex — Ex — Ex Electrode 8.5 10.0 9.0 10.5 9.0 10.5 9.0 Connector 8.0 15.0 15.0 15.0 15.0 15.0 15.0 14.0 14.0 14.0 14.0 14.0 14.0 14.0 14.0 14.0 14.0 14.0 15.3 1.53 1.53 1.53 1.53 1.53 1.53 1.53 1.70</td></t<>	75~130 150~225 250~300 350 Excellent — Ex — Ex — Ex Electrode 8.5 10.0 9.0 10.5 9.0 10.5 9.0 Connector 8.0 15.0 15.0 15.0 15.0 15.0 15.0 14.0 14.0 14.0 14.0 14.0 14.0 14.0 14.0 14.0 14.0 14.0 15.3 1.53 1.53 1.53 1.53 1.53 1.53 1.53 1.70	

High Power Graphite Electrodes

iigh i ower drupinte Licotrodes			
ltem		N	lominal diameter mm
		200~400	450~500
Resistivity	Electrode	7.0	7.5
μΩ·m≤	Connector	6.3	6.3
Flexural strength MPa ≥	Electrode	10.5	10.0
Flexulal Strength WFa 2	Connector	17.0	17.0
Elastic Modulus GPa <	Electrode	14.0	14.0
Elastic Modulus GFa S	Connector	16.0	16.0
Dulk danaity a/am2 >	Electrode	1.60	1.60
Bulk density g/cm3 ≥	Connector	1.72	1.72
Thermal expansion coefficient 10-6/	Electrode	2.4	2.4
Room temperature~600 ≥	Connector	2.2	2.2
Ash % ≤	·	0.5	0.5

Ultra High Power Graphite Electrode

ltem		Nominal diameter mm			
		300~400	450~500	550~650	
Resistivity	Electrode	6.2	6.3	6.0	
μΩ·m ≤	Connector	5.3	5.3	4.5	
Flexural strength MPa ≥	Electrode	10.5	10.5	10.0	
	Connector	20.0	20.0	22.0	

Elastic Modulus GPa ≤	Electrode	14.0	14.0	1.66
Elastic Modulus GFa 5	Connector	20.0	20.0	1.78
Bulk density g/cm3 ≥	Electrode	1.67	1.66	1.66
Duik defisity g/cmo 2	Connector	1.74	1.75	1.78
Thermal expansion coefficient 10-6/	Electrode	1.5	1.5	1.5
Room temperature~600 ≥	Connector	1.4	1.4	1.3
Ash % ≤		0.5	0.5	0.5

Quality Assurance

We adhere to strict quality control standards throughout the manufacturing process, ensuring each product meets international requirements. With over 20 years of experience in the refractory materials sector, we pride ourselves on delivering reliable solutions.

Why Choose Rongsheng RP HP UHP Grades Available Graphite Electrode Nipples?

Industry Expertise: With two decades of experience, we are recognized as leaders in the refractory materials market.

Global Distribution: Our products are exported to over 100 countries, making us a trusted supplier worldwide. **Dedicated Customer Support**: We offer personalized solutions and attentive service to meet your specific needs.

Contact Information

For inquiries or to place an order, please contact us:

Tel/Whatsapp: +86-18538509097 Email:Jackyhan2023@outlook.com

Explore the advantages of our Graphite Electrode Nipples today and enhance your production processes with our reliable solutions!

