



Wear-Resistant Silica-Mullite Brick High Temperature Compressive Strength Furnace Refractory Brick

Our Product Introduction

for more products please visit us on bricksrefractory.com

Basic Information

- Place of Origin: Zhengzhou ,China
- Brand Name: Rongsheng Xinwei
- Certification: ISO9001
- Model Number: RS-AZM1650, RS-AZM1680
- Minimum Order Quantity: 1 Ton
- Price: 200-800USD
- Packaging Details: Packed on wooden pallets, with water-proof cover, and tightened with plastic/steel bandages
- Delivery Time: 10-20 Days
- Payment Terms: TT; L/C
- Supply Ability: 2000tons /month



Product Specification

- Highlight: **Silica Mullite Furnace Refractory Brick, Wear Resistant Furnace Refractory Brick**

Product Description

Product Overview of Wear-Resistant Silica-Mullite Brick High Temperature Compressive Strength Furnace Refractory Brick

Silica-mullite brick is crafted using sintered bauxite and high-density silicon carbide (SiC) through a process of pressing and high-temperature firing.

These bricks stand out for their excellent thermal shock resistance, superior wear resistance, and strong spalling resistance, making them an ideal choice for cement kilns. They are commonly used in the transition zone, cooling zone, and kiln outlet.

If you're looking for a reliable supplier of silica mullite bricks at competitive prices from China, Rongsheng Refractory is here to assist you. Feel free to reach out to us for a free quotation!

Our Product Introduction



Characteristics of Superior Quality Silica Mullite Bricks

High Strength: Designed to endure high-pressure operations.

Superior Wear Resistance: Performs well in abrasive conditions.

Outstanding Thermal Shock Resistance: Maintains stability during rapid temperature changes.

Extended Service Life: Ensures a prolonged operational lifespan.

Applications of Wear-Resistant Silica-Mullite Brick High Temperature Compressive Strength Furnace Refractory Brick

High-quality silica-mullite bricks are considered the top refractory material for large cement kilns, particularly in the:

- Transition zone
- Calcining zone
- Cooling zone

Product Specification of Superior Quality Silica Mullite Bricks

Item	RS-AZM1650	RS-AZN
SiC + SiO ₂	≥ 30	≥ 3
Al ₂ O ₃	≥ 65	≥ 6
Refractoriness Under Load	≥ 1650	≥ 16
Apparent Porosity (%)	≤ 19	≤ 1
Thermal Shock Resistance	≥ 15	≥ 2
Bulk Density (g/cm ³)	≥ 2.65	≥ 2.7
Cold Crushing Strength (Mpa)	≥ 90	≥ 10



Henan Rongsheng Xinwei New Materials Research Institute Co., Ltd

+86-18538509097

Jackyhan2023@outlook.com

bricksrefractory.com

11th Floors, Building 6, China Central Electronic Commerce Port, Daxue Road, Zhengzhou, Henan, China