

High Temperature Resistance High Alumina Brick Curved Arched Fire Brick Insulating Fireclay Refractory For furnace

packed on wooden pallets, with water-proof cover, and tightened with plastic/steel

for more products please visit us on bricksrefractory.com

Basic Information • Place of Origin: Zhengzhou ,China • Brand Name: Rongsheng Xinwei • Certification: ISO9001 • Model Number: RS-48, RS-55, RS-65, RS-75, RS-80 • Minimum Order Quantity: 1 Ton

- 200-800USD
- Price: Packaging Details:
- Delivery Time:
- Payment Terms: TT; L/C
- Supply Ability:

Product Specification

Application Temperature:	≤1400
 Bulk Density: 	≥2.0g/cm3
Chemical Composition:	AI2O3≥60%
Cold Crushing Strength:	≥20MPa
Color:	Red
Compressive Strength:	≥50MPa
Density:	2.4-2.6g/cm3
 Linear Change Rate: 	≤0.2%
 Material: 	High Alumina Refractory Brick
 Porosity: 	≤18%
Refractoriness:	≥1700
• Shape:	Rectangular
• Size:	Standard
Thormal Conductivity	<1.2W/m K

bandages 20-30DAYS

2000tons /month

- Thermal Conductivity: ≤1.2W/m.K
- Thermal Shock Resistance: Good

More Images



Product Description

Description of High Temperature resistance High Alumina Brick Curved Arched Fire Brick Insulating Fireclay Refractory For furnace

High alumina bricks refer to aluminosilicate refractory products with aluminum oxide (Al2O3) content higher than 48%. It belongs to neutral refractory material. It is formed by shaping and calcining bauxite or other raw materials with high alumina content. High thermal stability and fire resistance above 1770. It has good slag resistance and is used for lining steel making electric furnace, glass furnace, cement rotary furnace, etc.

High load soft and low creep high alumina brick is a high-grade refractory material made of special grade bauxite, fused corundum and fused mullite. The product has the advantages of small high-temperature creep, strong corrosion resistance, good thermal shock stability, etc. It is suitable for large and medium-sized hot blast furnaces.



Advantage of High Temperature resistance High Alumina Brick Curved Arched Fire Brick Insulating Fireclay Refractory For furnace

- 1. High refractoriness;
- 2. High temperature strength;
- 3. High thermal stability;
- 4. Neutral refractory;5. Good resistance to acid and basic slag corrosion;
- 6. High refractoriness under load;
- 7. High temperature creep resistance;
- 8. Low apparent porosity;

Application of High Temperature resistance High Alumina Brick Curved Arched Fire Brick Insulating Fireclay Refractory For furnace

As a basic material in the field of high-temperature technology, high alumina bricks are widely used in cement, glass building materials, steel smelting, petrochemical and other industries. High temperature industrial furnaces for high alumina bricks include blast furnace, hot blast furnace, electric furnace, blast furnace, reverberatory furnace and rotary kiln lining. In addition, high alumina bricks can also be processed into open hearth regenerative grid bricks, socket bricks for pouring system, nozzle bricks, etc. according to the requirements of industrial furnaces.

Parameter of High Alumina Brick Curved Arched Fire Brick Insulating Fireclay Refractory For furnace

Item Al2O3 (%)		Properties			
		RS-80	RS-75	RS-65	RS-55
		80	≥75	≥65	≥55
Refractoriness (°C)		≥1790	≥1790	≥1790	≥177(
Bulk density (g/cm3)		2.65	2.5	2.45	2.4
Softening temperature under load (°C)	1530	≥1520	≥1500	≥147(
Linear changes on reheating (%)	1500°CX2H	0.1	0.1	0.1	0.1
	1500 07211	-0.4	-0.4	-0.4	-0.4
	1450°CX2H				
Apparent porosity (%)	Apparent porosity (%) Cold crushing strength (Mpa)		≤23	≤23	≤22
Cold crushing strength (Mpa)			≥50	≥45	≥40

۲ Henan Rongsheng Xinwei New Materials Research Institute Co., Ltd

+86-18538509097 Jackyhan2023@outlook.com

bricksrefractory.com

11th Floors, Building 6, China Central Electronic Commerce Port, Daxue Road, Zhengzhou, Henan, China

for more products please visit us on bricksrefractory.com