Nano Insulating Castable Material Ultra Lightweight Lightweight Castable Refractory

Basic Information

Place of Origin: Zhengzhou, Henan, China
 Brand Name: Rongsheng Xinwei
 Certification: ISO Certification

Model Number: RS-CQJ0.35, RS-CQJ0.45, RS-CQJ0.5

Minimum Order Quantity: 1 TonPrice: 200-800 USD

• Packaging Details: packed on wooden pallets, with water-proof

cover, and tightened with plastic/steel bandages

Delivery Time: 20-30DAYS
Payment Terms: TT; L/C
Supply Ability: 2000tons /month



Product Specification

Acid Resistance: No Degradation
 Alkali Resistance: No Degradation
 Compressive Strength: 0.4MPa
 Elongation: 300%
 Flammability: Class A1

Material: Nano Insulation Material

Radiation Resistance: No Degradation
 Smoke Density: Class 0
 Temperature Resistance: -50 ~+150
 Tensile Strength: 2.0MPa

Thermal Conductivity: 0.038W/mK
Thermal Resistance: 0.26m2K/W
Thickness: 1mm
Water Vapor Permeability: 2.0g/m2/24h
Weight: 100g/m2

Product Description

Ultra-lightweight Insulating Castable Series

The ultra-lightweight insulating castable developed by Rongsheng is made of high-temperature high-strength light-weight nano-aggregate, aluminate cement and high-alumina fines with various additives, which has the advantages of small bulk density, high crushing strength, low thermal conductivity, excellent thermal insulation, energy saving and consumption reduction, convenient construction, and so on. It can reduce the thermal energy consumption of industrial furnaces and reduce the weight of furnace lining.

Parameter of Ultra-lightweight Insulating Castable Series

Items		RS-CQJ0.35	RS-CQJ0.45	R
BD, g/cm3	110 ×24h	≤0.35	≤0.45	

CCS, MPa	110 ×24h	≥0.5	≥0.8	3
TC,W/(m·K)	350 ±25	≤0.11	≤0.15	≤
PLC,%		-0.1~+0.1 1000 ×12h	-0.1~+0.1 1100 ×12h	-0.2~+0.2
Max Working Temperature,		1000	1100	1

##