for more products please visit us on bricksrefractory.com

Low Porosity Fireclay Bricks For Modern Industrial

Basic Information

• Place of Origin: Zhengzhou, China • Brand Name: Rongsheng Xinwei

• Certification: ISO9001 Model Number: Rongsheng Minimum Order Quantity: 1 Ton • Price: 200-800USD

• Packaging Details: Packed on wooden pallets, with water-proof cover, and tightened with plastic/steel bandages

20-30 Days • Delivery Time: • Payment Terms: TT; L/C 2000 tons/month Supply Ability:



Product Specification

• Highlight: Modern Industrial Fireclay Bricks, Industrial Fireclay Bricks

Product Description

Introduction:

Low porosity fireclay bricks are essential in modern industrial applications where efficiency and reliability are critical. Their advanced properties make them suitable for a variety of high-temperature environments, ensuring optimal performance and durability.

Product Features:

Low Porosity: Enhances thermal insulation, reduces heat loss, and improves energy efficiency.

Thermal Shock Resistance: Withstands rapid temperature changes and harsh conditions, maintaining performance over time. Mechanical Strength: Offers high compressive strength and durability, essential for industrial applications.



Applications:

High-Temperature Kilns: Used in kilns for ceramics, glass, and other materials where consistent temperature control is needed. Furnaces and Boilers: Ideal for use in industrial furnaces and boilers, providing reliable thermal management and energy

Reactor Linings: Suitable for lining chemical reactors where high thermal stability and chemical resistance are required. Advantages:

Enhanced Performance: Superior insulation and thermal shock resistance lead to better overall performance in hightemperature processes.

Cost Efficiency: Reduced energy consumption and extended service life offer significant cost savings and improved ROI. Versatility: Applicable across various industries and processes, making them a versatile choice for different applications.

Product Specification of Low Porosite Fireclay Bricks

······································		
ltem	Inde	x
Al ₂ O ₃ %	≥45	
Fe ₂ O ₃ %	≤1.3	
Bulk Density g/cm ³	≥2.3	
Apparent Porosity %	≤16	
Cold Crushing Strength MPa	≥65	
Creep rate % 1200 ×50h	≤0.0	5
Thermal shock resistance cycle 1100 water cooling	10	

Henan Rongsheng Xinwei New Materials Research Institute Co., Ltd





