

Good Quality Best Price Calcined Bauxite High Alumina Calcined Aluminum **Bauxite For Sale**

Basic Information

• Place of Origin: Zhengzhou ,China • Brand Name: Rongsheng Xinwei • Certification: ISO9001 Model Number: Rongsheng • Minimum Order Quantity: 1 Ton • Price: 200-800USD • Packaging Details: Packed on wooden pallets, with water-proof cover, and tightened with plastic/steel bandages 10-20 Days • Delivery Time: TT; L/C

2000tons /month

- Payment Terms:
- Supply Ability:

Product Specification

Product Description

Our Product Introduc

Product Description of Good Quality Best Price Calcined Bauxite High Alumina Calcined Aluminum **Bauxite For Sale**

Calcined Bauxite is produced through the high-temperature sintering of high-alumina bauxite in rotary, shaft, or round kilns. This calcination procedure expels moisture from the bauxite, boosting its alumina content and enhancing its refractoriness. The end product is a material with lower iron content, superior grain hardness, and toughness. Thanks to its impressive thermal stability and resistance to molten slags, Calcined Bauxite is a vital raw material for a wide range of applications, including the production of advanced refractory materials, abrasives, and other specialized products that demand high mechanical strength and performance under extreme conditions.

Physical And Chemical Index of High Alumina Calcined Bauxite Powder

Product Code		Chemical	Compos	sition (Mass Frac	Dulle Danaite a /anai	
	AI2O3	Fe2O3	TiO2	CaO+MgO	K2O+Na2O	Bulk Density g/cm'

>89.5	<15	<10	<0.35	<0.35	>3 35	≤2.5
≥87.5	≤1.6	≤4.0	≤0.4	≤0.4	≥3.20	≤3.0
≥87.5	≤2.0	≤4.0	≤0.4	≤0.4	≥3.25	≤3.0
≥85	≤1.8	≤4.0	≤0.4	≤0.4	≥3.10	≤3.0
≥85	≤2.0	≤4.5	≤0.4	≤0.4	≥2.90	≤5.0
>80	≤2.0	≤4.0	≤0.5	≤0.5	≥2.90	≤5.0
70~80	≤2.0	—	≤0.6	≤0.6	≥2.75	≤5.0
60~70	≤2.0		≤0.6	≤0.6	≥2.65	≤5.0
50~60	≤2.5	_	≤0.6	≤0.6	≥2.55	≤5.0
	≥85 ≥85 >80 70~80 60~70	≥87.5 ≤1.6 ≥87.5 ≤2.0 ≥85 ≤1.8 ≥85 ≤2.0 >80 ≤2.0 70~80 ≤2.0 60~70 ≤2.0	≥87.5 ≤1.6 ≤4.0 ≥87.5 ≤2.0 ≤4.0 ≥85 ≤1.8 ≤4.0 ≥85 ≤2.0 ≤4.5 >80 ≤2.0 ≤4.0 70~80 ≤2.0 60~70 ≤2.0	≥ 87.5 ≤ 1.6 ≤ 4.0 ≤ 0.4 ≥ 87.5 ≤ 2.0 ≤ 4.0 ≤ 0.4 ≥ 85 ≤ 1.8 ≤ 4.0 ≤ 0.4 ≥ 85 ≤ 2.0 ≤ 4.5 ≤ 0.4 ≥ 85 ≤ 2.0 ≤ 4.5 ≤ 0.4 > 80 ≤ 2.0 ≤ 4.0 ≤ 0.5 $70~80$ ≤ 2.0 $$ ≤ 0.6 $60~70$ ≤ 2.0 $$ ≤ 0.6	≥ 87.5 ≤ 1.6 ≤ 4.0 ≤ 0.4 ≤ 0.4 ≥ 87.5 ≤ 2.0 ≤ 4.0 ≤ 0.4 ≤ 0.4 ≥ 85 ≤ 1.8 ≤ 4.0 ≤ 0.4 ≤ 0.4 ≥ 85 ≤ 1.8 ≤ 4.0 ≤ 0.4 ≤ 0.4 ≥ 85 ≤ 2.0 ≤ 4.5 ≤ 0.4 ≤ 0.4 ≥ 86 ≤ 2.0 ≤ 4.0 ≤ 0.5 ≤ 0.5 $70^{-}80$ ≤ 2.0 $$ ≤ 0.6 ≤ 0.6 $60^{-}70$ ≤ 2.0 $$ ≤ 0.6 ≤ 0.6	$\begin{array}{c c c c c c c c c c c c c c c c c c c $

Section and the section of the secti

C +86-18538509097 S Jackyhan2023@outlook.com S bricksrefractory.com

11th Floors, Building 6, China Central Electronic Commerce Port, Daxue Road, Zhengzhou, Henan, China