for more products please visit us on bricksrefractory.com

# 65%-95% Al2O3 High Aluminum Refractory Ball For Oven Kiln Furnace

#### Basic Information

Place of Origin: Zhengzhou ,ChinaBrand Name: Rongsheng Xinwei

• Certification: ISO9001

• Model Number: RS-65, RS-70, RS-75, RS-95

Minimum Order Quantity: 1 TonPrice: 200-800USD

Packaging Details: packed on wooden pallets, with water-proof

cover, and tightened with plastic/steel

bandages 20-30DAYS TT; L/C

• Supply Ability: 2000tons /month



### **Product Specification**

Delivery Time:Payment Terms:

Al2O3 Content: ≥48%
Application Temperature: ≤1400
Bending Strength: ≥25MPa
Color: Red
Compressive Strength: ≥50MPa
Density: 2.2-2.4g/cm3
Fe2O3 Content: ≤2.5%

Material: High Alumina Refractory Brick

Refractoriness: ≥1790
Refractoriness Under Load: ≥1450
Shape: Rectangle
SiO2 Content: ≤40%
Size: Customized
Thermal Conductivity: ≤0.6W/m.k
Thermal Shock Resistance: Good

### **Product Description**

## Description of 65%-95% Al2O3 High Aluminum Refractory Ball For Oven Kiln Furnace

Refractory balls are made of industrial alumina and refractory kaolin as the main raw materials, which are made by scientific formula, forming and hightemperature calcination.

Refractory ball is divided into ordinary refractory ball and high aluminum resistance ball. Refractory porcelain ball high temperature resistance to high temperature can reach 1900 degrees, high mechanical strength and long-term use.

#### **High Alumina Refractory Ball Features**

- 1. high temperature resistant performance, the highest heat resistant ceramic ball temperature can reach 1900 degrees;
- 2. high mechanical strength, long use cycle;
- 3. good chemical stability, no chemical reaction with the material;
- 4. good thermal stability, high strength;

#### **High Alumina Refractory Ball Applications**

High alumina ball application in chemical fertilizer plant of high and low temperature transformation furnace, reformer,

hydrogenation, desulfurization tank and methanation furnace, dispersed liquid, and supporting, covering and protecting catalyst role, can also be used in heating furnace of iron and steel industry and the transformation of equipment, ordinary refractory ball suitable for sulfuric acid and fertilizer industries converter and transform furnace, high aluminum refractory ball is suitable for industries such as steel, urea, hot blast furnace, heating and transformation furnace and other equipment.



Product Specification of 65%-95% Al2O3 High Aluminum Refractory Ball For Oven Kiln Furnace

Item	High alumina	Low creep	Mullite	
Size(mm)	40-80	40-80	40-80	
AL2O3(%)	65	70	75	
Refractoriness under load(°C)	1450	1460	1530	
Apparent Porosity(%)	25	23	22	
Bulk Density(g/cm3)	2.3	2.4	2.5	
Cold crushing strength(Mpa)	13	14	32	
Thermal shock resistance (1100°Cwater cooling) cycle ≥	15	10	20	
Refractoriness(°C)	1710	1750	1800	

Henan Rongsheng Xinwei New Materials Research Institute Co., Ltd



+86-18538509097 Sackyhan2023@outlook.com



bricksrefractory.com

11th Floors, Building 6, China Central Electronic Commerce Port, Daxue Road, Zhengzhou, Henan, China