

Refractory Factory Production Ceramic Fiber Rope Ceramic Fiber Cord Low Density

Ceramic fiber round braided rope, Ceramic

30 Metric Ton/Metric Tons Per Day

fiber square braided rope

for more products please visit us on bricksrefractory.com

Basic Information • Place of Origin: Zhengzhou, Henan, China • Brand Name: Rongsheng Xinwei • Certification: ISO Certification

Model Number:

• Price:

- Minimum Order Quantity: 5 Kilograms
 - \$1.80 \$6.00
- Packaging Details:
 1.Carton with inner PVC bags carton.
 2.Woven bags with inner PVC bags.

10-20 Days

TT; L/C

- Delivery Time:
- Payment Terms:
- Supply Ability:

Product Specification Color: White • Cost: Cost-Effective Density: Low Density Durability: High Durability Flexibility: High Flexibility Insulation: Excellent Insulation . Length: Various Lengths Material: Ceramic Fiber • Resistance: High Resistance Shape: Various Shapes Size: Various Sizes • Surface: Smooth Surface • Temperature: High Temperature • Thickness: Various Thickness • Width: Various Widths

Product Description

Description of Good Price Refractory Factory Production Ceramic Fiber Rope

Ceramic fiber rope is made from high quality ceramic fiber yarn, with light weight, good flexibility. It has two type, glass filament reinforced and stainless stainless steel reinforced, can be widely used in industrial heat insulation.

Features of Ceramic Fiber Rope

- 1. High density, neat and delicate.
- 2. Quality material selection, strict workmanship.
- 3. Has good corrosion resistance.

Applications Of Ceramic Fiber Rope Industrial furnace, used for industrial furnace curtain, furnace door seal

High temperature cable, pipeline wrapping Metallurgy, power petrochemical industry Fire doors, fire curtains, fire blankets, spark MATS and thermal insulation coverings

for more products please visit us on bricksrefractory.com

Classification temperature	1260			
Name	Ceramic fiber round braided rope		Ceramic fiber square braided ro	
Brand	XSY-A	XSY-B	XSF-A	X
Main material	Ceramic fiber/glass fiber	Ceramic fiber/stainless steel wire	Ceramic fiber/glass fiber	Ceramic fiber/s
Bulk Density kg/m ³	500			
Size	200000/50000×10/25/30		10000×(20×20/30×30)	
Long term service temperature	650	1050	600	1
Moisture content %	≤2			
Organic content %	≤15			

Second state of a weil Henan Rongsheng Xinwei New Materials Research Institute Co., Ltd

C +86-18538509097 S Jackyhan2023@outlook.com bricksrefractory.com

11th Floors, Building 6, China Central Electronic Commerce Port, Daxue Road, Zhengzhou, Henan, China