Our Product Introduc

High Oxide Aluminium Standard Refractory Brick With Temperature Resistance 1770

Basic Information

Place of Origin: Zhengzhou ,ChinaBrand Name: Rongsheng Xinwei

• Certification: ISO9001

• Model Number: RS-48, RS-55, RS-65, RS-75, RS-80

Minimum Order Quantity: 1 TonPrice: 200-800USD

Packaging Details: packed on wooden pallets, with water-proof

cover, and tightened with plastic/steel bandages

Delivery Time: 20-30DAYS
 Payment Terms: TT; L/C
 Supply Ability: 2000tons /month



Product Specification

Application: High Temperature Furnace

Bulk Density: High
Chemical Resistance: Good
Cold Crushing Strength: High
Color: Red
Compressive Strength: High

Material: High Alumina Refractory Brick

Porosity: Low
Refractoriness: High
Shape: Rectangular
Size: Standard
Surface: Smooth
Thermal Conductivity: Low
Thermal Expansion: Low
Thermal Shock Resistance: Good



More Images





Product Description

Descripton of High Oxide Aluminium Standard Refractory Brick With Temperature Resistance 1770

High Alumina Bricks, crafted from premium-grade raw materials with an alumina content exceeding 48%, are the epitome of superior refractory materials. These bricks boast exceptional thermal stability and refractoriness, withstanding temperatures in excess of 1770. Renowned for their high strength and resistance to acid and erosion, they find applications in diverse industries including cement, glass, steel, and petrochemicals. With a composition tailored for neutral refractoriness, they ensure reliable performance in environments exceeding 1300 degrees centigrade. Explore our range of High Alumina Bricks, meticulously engineered to meet the stringent demands of high-temperature technology.



Feature of High Oxide Aluminium Standard Refractory Brick With Temperature Resistance 1770

1. Good thermal conductivity. 2. High fire resistance. 3. Good slag resistance, acid and alkali resistance. 4. Thermal stability.

High alumina bricks find extensive application in industries that involve high-temperature processes and environments. These bricks, composed primarily of alumina (Al2O3), possess remarkable refractory properties, making them ideal for use in various industrial settings. Some common applications include:

Steel Industry, Cement Industry, Glass Industry, Petrochemical Industry, Non-Ferrous Metal Industry, Power Generation, Ceramics Industry, Incinerators and Waste Management, Refractory Constructions.

Other Specialized Applications: High alumina bricks can be customized and utilized in a wide range of specialized applications, including in the aerospace, automotive, and chemical processing industries.

Overall, high alumina bricks are an integral part of many industries that rely on high-temperature processes, offering durability, thermal stability, and resistance to harsh environments.

Product Specification of High Alumina Bricks Standard Refractory Brick

ltem	Specification				
	LZ-80	LZ-75	LZ-70	LZ-65	LZ-55
Al2O3 %	≥80	≥75	≥70	≥65	≥55
Apparent Porosity, %	≤21	≤24	≤24	≤24	≤22
CCS, MPa	≥70	≥60	≥55	≥50	≥45
0.2MPa RUL	≥1530	≥1520	≥1510	≥1500	≥1450
PLC, %	1500 ×2h		1450 ×2h		
	-0.4~0.2		-0.4~0.1		4~0.1

Henan Rongsheng Xinwei New Materials Research Institute Co., Ltd

+86-1853850909

Jackyhan2023@outlook.com

bricksrefractory.com

11th Floors, Building 6, China Central Electronic Commerce Port, Daxue Road, Zhengzhou, Henan, China