

## Medium High Alumina Refractory Ball Refractory Ceramic Ball For Hot Blast Stove

Our Product Introduction

for more products please visit us on [bricksrefractory.com](http://bricksrefractory.com)

### Basic Information

- Place of Origin: Zhengzhou ,China
- Brand Name: Rongsheng Xinwei
- Certification: ISO9001
- Model Number: Rongsheng
- Minimum Order Quantity: 1 Ton
- Price: 200-800USD
- Packaging Details: packed on wooden pallets, with water-proof cover, and tightened with plastic/steel bandages
- Delivery Time: 20-30DAYS
- Payment Terms: TT; L/C
- Supply Ability: 2000tons /month




### Product Specification

- Abrasion Resistance: High
- Al<sub>2</sub>O<sub>3</sub> Content: High
- Brick Type: Refractory
- Bulk Density: High
- Chemical Resistance: High
- Cold Crushing Strength: High
- Material: High Alumina
- Moisture Absorption: Low
- Porosity: Low
- Refractoriness: High
- Shape: Brick
- Thermal Conductivity: Low
- Thermal Expansion: Low
- Thermal Shock Resistance: High
- Working Temperature: High



### More Images



### Product Description

#### Product Description of Medium And High Alumina Refractory Ball For Hot Blast Stove Refractory Heat Storage Ball For Alumina Filler

Refractory high alumina balls are made of industrial alumina and refractory kaolin as the main raw materials, which are made by scientific formula, forming and hightemperature calcination.

Refractory alumina ball is divided into ordinary refractory ball and high aluminum resistance ball. Refractory porcelain ball high temperature resistance to high temperature can reach 1900 degrees, high mechanical strength and long-term use.

Our Product Introduction



#### High Alumina Refractory Ball Features

1. high temperature resistant performance, the highest heat resistant ceramic ball temperature can reach 1900 degrees;
2. high mechanical strength, long use cycle;
3. good chemical stability, no chemical reaction with the material;
4. good thermal stability, high strength;

#### High Alumina Refractory Ball Applications

High alumina ball application in chemical fertilizer plant of high and low temperature transformation furnace, reformer, hydrogenation, desulfurization tank and methanation furnace, dispersed liquid, and supporting, covering and protecting catalyst role, can also be used in heating furnace of iron and steel industry and the transformation of equipment, ordinary refractory ball suitable for sulfuric acid and fertilizer industries converter and transform furnace, high aluminum refractory ball is suitable for industries such as steel, urea, hot blast furnace, heating and transformation furnace and other equipment.

#### Product Specification of High Alumina Refractory Ball

Item	High alumina	Low creep	Mullite	
Size(mm)	40-80	40-80	40-80	
AL <sub>2</sub> O <sub>3</sub> (%)	65	70	75	
Refractoriness under load(°C)	1450	1460	1530	
Apparent Porosity(%)	25	23	22	
Bulk Density(g/cm <sup>3</sup> )	2.3	2.4	2.5	
Cold crushing strength(Mpa)	13	14	32	
Thermal shock resistance (1100°Cwater cooling) cycle ≥	15	10	20	
Refractoriness(°C)	1710	1750	1800	



**Henan Rongsheng Xinwei New Materials Research Institute Co., Ltd**



+86-18538509097



Jackyhan2023@outlook.com



[bricksrefractory.com](http://bricksrefractory.com)

11th Floors, Building 6, China Central Electronic Commerce Port, Daxue Road, Zhengzhou, Henan, China